



吸貼裝置
Tamp labeling device



自動送料整列機構
Automatic material arraying device



前後調整手輪
& 位置顯示器
Front / Back adjusting device & Position indicator



• 星盤機構
Indexing system
• 漏標檢測電眼
Label missing detection sensor



漏標自動剔除裝置
Automatic rejection device for missing-label product

LA-750 自動吸貼式上貼貼標機 (星盤式 / 自動送料)

Automatic Top Tamp Labeling Machine (Indexing type / Automatic feeding system)

適用範圍

- 星盤式設計，適用不易站立或特殊造型之產品上方貼標。
- 吸貼式貼標之精準度極高，適合非常要求貼標精度之產品。
- 適合各種材質較小與較大標籤尺寸，同時適用透明標籤。
- 適合單項產品產量較大之生產需求。

特色介紹

- 日本三菱 PLC，搭配 7 吋彩色人機觸控螢幕，操作簡易。
- 出標系統：採用步進馬達，貼標精準度高，易於校正控制。
- 便利手輪裝置搭配位置顯示器，輕鬆調整與記錄貼標位置。
- 內建 50 組記憶模組，適合生產多種產品，不需重覆設定。
- 使用者友善設計，免工具即可快速進行多數的調校或拆卸。
- 自動送料系統：免除人工送料，可大幅提升產能與降低成本。
- 德國 SICK 電眼：偵測產品尺寸未在設定範圍內，不進行貼標。
- 漏標自動剔除裝置：未貼標之產品將被剔除，提高生產良率。

機台規格

機台尺寸	1800(長) x 1500(寬) x 1700(高) mm
動力需求	電壓 220V，頻率 50/60Hz，單相，視在功率 1.13KVA
需求空壓	5kg/cm ² 以上 (請自備空壓來源)
適用標籤高度	(A 型)10~100 (B 型)10~150 mm
適用標籤長度	10 ~ 75 mm
機台產能	約 10 ~ 15 個 / 每分鐘
貼標精度	± 0.5 mm
印字設備 (選配)	(1) 熱燙印字機 / 熱轉印機 / 噴印機 (印日期、批號、條碼... 另含可調整支撐座) (2) 數位全彩標籤列印機 (即印即貼整張標籤 / 300 dpi 超高列印解析度)

Field of Application

- Indexing design is suitable for top labeling on products which are difficult to stand stably or with special shapes.
- Tamp labeling offers excellent labeling performance for products require high labeling precision.
- For larger or smaller label size with different material, transparent labels are also applicable.
- Applicable larger production volume of single product.

Features

- Mitsubishi PLC and 7" color touch screen (HMI) provide convenient operation.
- Labeling system: Stepper motor offers high labeling precision.
- Adjust and record the labeling position conveniently by a hand-wheel device combined with position indicator.
- 50 sets of memory storage: Perfect for various products without repeated setting.
- User-friendly design: Most adjustments can be finished easily without using tools.
- Automatic feeding device: Improve production efficiency. Products are fed automatically, labor costs are saved a lot!
- SICK photoelectric sensor (German brand) helps to stop labeling for those products which are detected not in the allowed product size range.
- Automatic missing-label rejection device: Reject the products which are not labeled.

Specifications

Machine Dimension	1800(L) x 1500(W) x 1700(H) mm
Power Requirement	220V, 50/60Hz, 1 Phase, 1.13KVA
Pneumatic Requirement	5kg/cm ² at least (prepared by buyer)
Applicable Label Height	(A) 10~100 (B) 10~150 mm
Applicable Label Length	10 ~ 75 mm
Production Capacity	About 10 ~ 15 PCS / per minute
Labeling Precision	± 0.5 mm
Printers (optional item)	(1) Hot Stamping / Heat Transfer / Inkjet (for Date, Batch no., Barcode... Support rack included) (2) Digital Color Label Printing (Print & Apply / Print resolution 300 dpi)