



熱燙印字機 & 可調支撐座 (選配)  
Hot stamping printer & Adjustable support rack (optional item)

收料斜板 & 靜電消除裝置 (選配)  
Collecting plate & Electrostatic elimination device (optional item)

前後調整手輪 & 位置顯示器  
Front / Back adjusting device & Position indicator



貼標機搭配熱轉印機 (包含：調整支撐座)  
Compatible with Heat Transfer Printer (Adjustable support rack included)

# LA-100 自動上貼貼標機

## Automatic Top Labeling Machine

### 適用範圍

- 產品上方之平面貼標，適合：方瓶 / 紙盒 / 塑料袋 / 面膜袋 / 卡片與說明書等各式產品。
- 適用多種標籤尺寸，亦適用透明標籤。
- 適合產品多樣化的貼標需求，可連線生產或單機使用。

### 特色介紹

- 日本三菱 PLC，搭配 7 吋彩色人機觸控螢幕，操作簡易。
- 出標系統採用步進馬達，貼標精準度高，易於校正控制。
- 便利手輪裝置搭配位置顯示器，輕鬆調整與記錄貼標位置。
- 內建 50 組記憶模組，適合生產多種產品，不需重覆輸入設定。
- 使用者友善介面：多種免工具調整設計，換線快速。
- 產品厚度 2 mm 以下，搭配「自動下料機」，大幅提升產能。
- 適合搭配「熱轉印機」與「噴印機」，可整合多家知名廠牌。

### 機台規格

機台尺寸	1700(長) x 550(寬) x 1650(高) mm
動力需求	電壓 110V，頻率 50/60Hz，單相，視在功率 150VA
適用標籤高度	(A 型)10~100 (B 型)10~150 (C 型)10~200 mm
適用標籤長度	10 ~ 200 mm
機台產能	約 10 ~ 25 米 / 每分鐘
貼標精度	± 1.0 mm
選配項目	(1) 印字設備：熱燙印字機 / 熱轉印機 / 噴印機 (印日期、批號、條碼... 另含可調整支撐座) (2) 收料斜板 (3) 靜電消除裝置

### Field of Application

- Labeling on the flat surface of various square bottles, boxes, plastic bags, cards, etc.
- A wide range of label size, transparent labels are also applicable.
- A wide range of products are applicable for a packaging production line or separate operation.

### Features

- Japan Mitsubishi PLC and 7" color touch screen (HMI) provide convenient operation.
- Stepper motor in labeling system offers the high labeling precision.
- Adjust and record the labeling position conveniently by a hand-wheel device combined with a position indicator.
- 50 sets of memory storage: Perfect for various products without repeated setting.
- User-friendly interface: Quick changeover design helps most adjustments can be finished without using tools.
- Recommend to combine with our Automatic Friction Feeder (AI-450) for product thickness below 2 mm, the production efficiency can be improved significantly.
- Compatible with Heat Transfer Printer or Inkjet Printer. Many famous brands of printer are available to be integrated.

### Specifications

Machine Dimension	1700(L) x 550(W) x 1650(H) mm
Power Requirement	110V, 50/60Hz, 1 Phase, 150VA
Applicable Label Height	(A) 10~100 (B) 10~150 (C) 10~200 mm
Applicable Label Length	10 ~ 200 mm
Production Capacity	About 10 ~ 25 meters / per minute
Labeling Precision	± 1.0 mm
Optional Item	(1) Printers : Hot Stamping / Heat Transfer / Inkjet (Date, Batch no., Barcode... Support rack included) (2) Collecting plate (3) Electrostatic elimination device