

貼標 Labeling  
 充填 Filling  
 鎖蓋 Capping  
 洗瓶 Rinsing  
 分張 Friction Feeder  
 光學檢測 Optical Inspection  
 鋁箔封口 Aluminum Foil Sealing  
 測漏 Leak Testing  
 面膜整平 Planishing  
 印字設備 Printing  
 快速運動護欄系統 Interlocking Guide Rail  
 整廠輸出 Turnkey Solution



控制面板  
Control panel

電磁感應線圈  
Induction coil

上下調整手輪 & 位置顯示器  
Up / Down adjusting device & Position indicator



工作台車 (選配)  
Working table (Optional item)

## CS-500 半自動瓶蓋鋁箔封口機 (電磁感應式)

### Semi-automatic Aluminum Foil Cap Sealing Machine (Induction coil type)

#### 適用範圍

- 適用內含鋁箔之瓶蓋來密封瓶口的塑膠類瓶罐產品。
- 適用瓶口直徑範圍大，不限容量或瓶型。
- 符合少量多樣的生產需求，大瓶小瓶一機搞定。

#### 特色介紹

- 採用非接觸性的電磁感應線圈，封口快速、擁有極佳密封品質。
- 控制面板標示清楚，可快速完成不同容器的設定調整。
- 便利手輪裝置搭配位置顯示器，免工具可輕鬆記錄與調整電磁感應線圈高低位置，適合各種不同高度的容器。
- 機台裝有過電流、過電壓、輸出過載、工作指示燈、故障蜂鳴器等保護裝置，安全第一好安心。
- 兩種啟動模式：可選擇「腳踏開關」或「電眼自動感應」啟動。
- 體積輕巧不佔空間，可任意更換擺放位置。

#### 機台規格

機台尺寸	500(長) x 500(寬) x 700(高) mm
動力需求	電壓 110V，頻率 50/60Hz，單相，視在功率 0.5KVA
適用瓶口直徑	Ø 20 ~ 120 mm
機台產能	約 10 ~ 15 瓶 / 每分鐘
適用瓶型	各式造型與容量之塑膠瓶罐
選配項目	工作台車 (桌面 # 304 不鏽鋼 / 附腳輪)

#### Field of Application

- For sealing the mouth of various plastic bottles and containers with aluminum foil which is inside plastic cap.
- Apply to a wide range of bottle mouth diameter for different bottle shape & volume.
- Small-volume production of a wide range of different products is most applicable.

#### Features

- Non-contact sealing induction coil offers excellent sealing quality and the shorter sealing time.
- Control panel is simple and user-friendly for convenient operation and quick changeover for different products.
- Sealing height of induction coil can be adjusted easily by a hand-wheel without using tools for different height of products.
- Many safety protection devices: Light signal, the siren for over-current, over-voltage, overload or breakdowns, etc.
- Two sealing start-up modes: Foot switch or a Photoelectric sensor.
- Lightweight design is suitable for moving the machine easily.

#### Specifications

Machine Dimension	500(L) x 500(W) x 700(H) mm
Power Requirement	110V, 50/60Hz, 1 Phase, 0.5KVA
Applicable Bottle Mouth Diameter	Ø 20 ~ 120 mm
Production Capacity	About 10 ~ 15 PCS / per minute
Applicable Bottle	Various shapes and volumes of plastic bottles.
Optional Item	Working table (Desktop #304 stainless steel / Castors attached)