



• 上下調整手輪 & 位置顯示器  
 Up / Down adjusting device & Position indicator

• 控制面板  
 Control panel

• 電磁感應線圈  
 Induction coil



工作台車 (選配)  
 Working table  
 (Optional item)

## CS-500 半自動瓶蓋鋁箔封口機 (電磁感應式)

### Semi-automatic Aluminum Foil Cap Sealing Machine (Induction coil type)

#### 適用範圍

- 適用內含鋁箔之瓶蓋來密封瓶口的塑膠類瓶罐產品。
- 適用瓶口直徑範圍大，不限容量或瓶型。
- 符合少量多樣的生產需求，大瓶小瓶一機搞定。

#### 特色介紹

- 採用非接觸性的電磁感應線圈，封口快速、擁有極佳密封品質。
- 控制面板標示清楚，可快速完成不同容器的設定調整。
- 便利手輪裝置搭配位置顯示器，免工具可輕鬆記錄與調整電磁感應線圈高低位置，適合各種不同高度的容器。
- 機台裝有過電流、過電壓、輸出過載、工作指示燈、故障蜂鳴器等保護裝置，安全第一好安心。
- 兩種啟動模式：可選擇「腳踏開關」或「電眼自動感應」啟動。
- 體積輕巧不佔空間，可任意更換擺放位置。

#### 機台規格

機台尺寸	500(長) x 500(寬) x 700(高) mm
動力需求	電壓 110V，頻率 50/60Hz，單相，視在功率 0.5KVA
適用瓶口直徑	∅ 20 ~ 120 mm
機台產能	約 10 ~ 15 瓶 / 每分鐘
適用瓶型	各式造型與容量之塑膠瓶罐
選配項目	工作台車 (桌面 # 304 不鏽鋼 / 附腳輪)

#### Field of Application

- For sealing the mouth of various plastic bottles and containers with aluminum foil which is inside plastic cap.
- Apply to a wide range of bottle mouth diameter for different bottle shape & volume.
- Small-volume production of a wide range of different products is most applicable.

#### Features

- Non-contact sealing induction coil offers excellent sealing quality and the shorter sealing time.
- Control panel is simple and user-friendly for convenient operation and quick changeover for different products.
- Sealing height of induction coil can be adjusted easily by a hand-wheel without using tools for different height of products.
- Many safety protection devices: Light signal, the siren for over-current, over-voltage, overload or breakdowns, etc.
- Two sealing start-up modes: Foot switch or a Photoelectric sensor.
- Lightweight design is suitable for moving the machine easily.

#### Specifications

Machine Dimension	500(L) x 500(W) x 700(H) mm
Power Requirement	110V, 50/60Hz, 1 Phase, 0.5KVA
Applicable Bottle Mouth Diameter	∅ 20 ~ 120 mm
Production Capacity	About 10 ~ 15 PCS / per minute
Applicable Bottle	Various shapes and volumes of plastic bottles.
Optional Item	Working table (Desktop #304 stainless steel / Castors attached)